

A KELLER TKO PUMP/SKIMMER RAPIDLY SWEEPS OUT TRAMP OIL, CLEANS AND AERATES THE ENTIRE SUMP

Get these benefits:

- Extended tool life, improved parts finish
- Smoke and odor eliminated
- Multiplied coolant life = Much less machine downtime, greatly reduced coolant purchase & disposal costs

With these exclusive Keller features

- Patented permanent oil separating (coalescing) element, never needs changing
- Rugged high flow 1/2" air-operated pump provides rapid tramp oil removal, circulates & aerates entire sump
- Compact inlet device can access any pump
- No electricals
- Sets up in minutes – Requires minimal operator attention

How the TKO Pump/Skimmer works:

The self-priming air operated pump pulls the tramp oil/coolant mixture from the surface of the sump through the floating inlet device, then through a cartridge filter which removes any chips from the fluid. The oil/coolant mixture is then pumped through the patented Keller all-plastic separator element immersed in a separator tank. The cleaned coolant continuously returns to the sump. The oil layer collects on the top of the separator tank and is occasionally drained into a waste oil container, simply by opening the oil drain valve. No other operator attention is required.



Model TKO-14. Footprint (all models) - 14" x 14"



Model TKO-6 mounted to machine tool with CLO-1 magnetic frame.

Selecting and Installing a TKO Separator:

Three models of TKO Separators are offered, to satisfy any sump size. Each TKO Separator is shipped by UPS complete, ready for setup. The customer supplies only a 1/4" compressed air line. The unit may be set on the floor adjacent to the sump, or mounted on the machine tool using the CLO-1 magnetic frame (see photo).

Ordering Information & Specifications

Ordering Designation	TKO-6	TKO-10	TKO-14
For Sump Sizes (gallon)	25-150	25-200	50-250
Footprint	14" x 14" (all models)		
Height	24"	30"	36"
Weight (empty)	35 lbs.	37 lbs.	43 lbs.
Compressed air requirements	0.5 SCFM @ 20 psig		

Accessory Items (All Models)

"Cling-On" frame with magnets, to mount TKO-6 to side of machine tool	CLO-1
Replaceable filter element, 150 micron, 10" long	R10-3150
Optional bag filter with 5 filter bags	BA-0475
Pack of 5 25-micron filter bags for BA-0475	RAP-25
<i>Additional Inlet Devices</i>	
Compact floating inlet device	#555-05
Fixed inlet device (Requires only 3" diameter access hole)	#555-06
Floating inlet device	#555-07
Small floating inlet device	#555-17